

SLE4428 Contact IC cards feature	<ul style="list-style-type: none"> <li>- SLE5542 Intelligent 256-Byte EEPROM</li> <li>- SLE5528 Intelligent 1K-Byte EEPROM</li> <li>- SLE4428 Intelligent 1K-Byte EEPROM</li> <li>- Write Protection function on unique manufacturer code to identification of application.</li> <li>- Programmable Security Code</li> <li>- EEPROM Endurance minimum 100,000 erase / write cycles</li> <li>- Minimum of 10 years data storage time</li> <li>- Contact configuration and serial interface in accordance to ISO standard 7816</li> </ul>
SLE4428 Contact IC cards Feature	<ul style="list-style-type: none"> <li>- Dimensions: CR80 85.60 x 53.98mm</li> <li>- Thickness: 0.84mm</li> <li>- Material: PVC, PET</li> <li>- Card Surface: Matte/ gloss finish</li> <li>- Housing: Lamination</li> <li>- Operating Temperature: -25 to +60°C</li> <li>- Storage Temperature: -40 to +70°C</li> </ul>
Printing Option	<ul style="list-style-type: none"> <li>- Full color offset printing</li> <li>- Silk-screen printing</li> <li>- Silver/Gold silk-screen printing background</li> </ul>
Additional crafts	<ul style="list-style-type: none"> <li>- Magnetic Stripe Option: 300oe, 2750oe, 4000oe</li> <li>- Numbering</li> <li>- Barcode printing</li> <li>- Signature panel</li> </ul>
Application	<ul style="list-style-type: none"> <li>- hotel key card, membership management</li> </ul>