

CJ2508A 802.11b UHF RFID 920MHz / 925MHz / 840MHz / 845MHz
 FCC 902MHz / 928MHz ETSI 865MHz / 868MHz JP 916MHz / 920MHz
 0dBm / 33dBm

RF Impinj R2000 ARM9 400MHz
 ISO18000-6B / 6C Linux 2.6
 RJ-45 / RS-232 / RS-485 / USB2.0 / Wiegand
 RSSI Bluetooth WIFI

Table

OS	Linux 2.6
CPU	ARM9,400MHz
Memory	DDR SDRAM 128M ROM 256M
Dimensions	255mm x 145mm x 35mm
Weight	1.4g
Power	DC 24V / 2.5A
UHF RFID	
Standard	ISO18000-6B / 6C
Frequencies	FCC 902 / 928MHz; ETSI 865 / 868MHz GB 920 / 925MHz / 840 / 845MHz
Power	0 / 33dBm ±1.5dBm
Antenna	1dB
Bandwidth	<200kHz
Accuracy	±10ppm
Interfaces	RS-232 RS-485 wiegand RJ45 USB2.0
Temperature	-40 to 85°C
RJ-45	10M / 100M
Read Range	> 400m
I/O	4 digital / 4 analog
Other	
RSSI	RSSI

□□□□□□□□□□	8□TNC□□□□□□□□□□
□□□□	□□□□□□□□
□□□□	0□15m□□□□□□□□□□□□□□□□
□□□□□□	0□7m□□□□□□□□□□□□□□□□
□□□□	
□□□□	-20□+ 70°C
□□□□	-40□+ 85°C
□□□	86kPa□108kPa
□□	5□95□RH□□□□□□
□□□□□	IP55

□□□□□□
□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□
□□□□□□□□□□□□□□□□;
□□□□□□□□□□□□□□□□