

CJ2712A FCC 频段(902~928MHz) 的 UHF RFID 天线，其 VSWR 在 45° 角时 ≤1.5，增益 ≥25dB，阻抗 50Ω，功率 100W，符合 FCC 认证要求。UHF RFID 天线，其 VSWR 在 45° 角时 ≤1.5，增益 ≥25dB，阻抗 50Ω，功率 100W，符合 FCC 认证要求。

型号:

工作频率: 902~928MHz

增益: 25dB

增益: 12dBi

工作电压:

工作电压	
工作频率	445mm×445mm×40mm
工作频率	60cm×48cm×11cm
工作频率	1.95kg
工作频率	3.95kg
工作频率	ABS
工作频率	ABS
工作频率	Φ40mm~80mm
工作频率	60m/
工作频率	-40~70℃
工作频率	
工作频率	902~928MHz
工作频率	12dBi
工作频率	45°, 45°
工作频率	
工作频率(VSWR)	≤1.5
工作频率	≥25
工作频率	50Ω
工作频率	100W
工作频率	N

01

Product lists: 1pc antenna,1pc power adaper,1pc plug,1pc data line,1pc installation bracket



Installation bracket



Power adapter/Plug



Data Line

02

Packaging Details:  
1 set 1 small case  
1 set package weight: 3.95kg  
Package size: 60cm×48cm×11cm



Inside packaging



one set packaging



5 sets packaging

## Applications:

Intelligent vehicle management  
Such as vehicle access control,  
non-stop charging, customs clearance,  
parking, auto weighing industry, etc;  
Production automation, visualization  
management;  
Logistics industry Such as container  
management, pallet management, etc.  
Access control system;  
Asset management, etc.

