

QR and RFID

1. Specification QR and RFID

Chip : NXP Ntag213, MIFARE S50, NXP, NXP C, 512

Standard : ISO 14443A

Frequency : 13.56 / HF

Reading distance : 3~10cm

2. Profile

Material : PVC / PET

Thickness : 0.84mm

Dimensions : 85.5 * 54 * 0.84mm

3. Working

Operating distance : 5~10cm

Temperature : -25 °C -50 °C

Humidity : 20 % -90 % RH

Storage temperature : -40 °C -65 °C

4. Craft

-preprinting : CMYK & ;

-signature

-magnetic : 3000OE, 2750OE, 4000OE

-barcode : CODE39, Code128, EAN8, EAN13,

-numbering : , ,

-encoding

5.

Material, , , ,

6. Packing

Quantity : 10boxes / 14kg (200PCS / 22.5 * 9.3 * 6cm)

Lead time : 10K 5-7

Shipping : (DHL,), ,

Trade terms : EXW, FOB, CIF, CNF

Payment : TT, ,

Quantity : 6,000,000pcs /

Standards : ISO9001-2008, SGS, ROHS, EN71.

QR and RFID



□ □□□ □□ :

* RFID □□□ □ NFC □□□ □□□□.

* TOP 10 2012 □□ □□□ □ Entreprenurs □.

* ISO9001-2008, ROHS, SGS□, EN71 □□□ □□

* □□□□ □□□ : NXP, □□, □□, □□□□ □□□ □□ □□, □□ □□ □

□□□ □□ □□□ □□□, pls□ □□□ □□ □□□□ □□□□. □□ □□ □□□□ □□ □□□□ □□ □ □□□□.