

CJ2504B RFID ISO18000-6C/6B
920MHz 925MHz 840MHz 845MHz FCC 902MHz 928MHz ETSI 865MHz 868MHz, JP 916MHz 920MHz 0dBm 33dBm

Impinj R2000 ARM9 400MHz ISO18000-6B/6C Linux2.6 RJ-45/RS-232/RS-485/USB2.0/ RSSI WIFI

	Linux 2.6
CPU	ARM9,400MHz
	DDR SDRAM128MROM256M
	255×145×35
	1.4
	DC 24V / 2.5A
UHF RFID	
	ISO18000-6B / 6C
	FCC902928MHz; ETSI865868MHz GB920925MHz840845MHz
	033dBm±1.5dBm
	1dB
	<200kHz
	≤±10ppm
	RS-232RS-485RJ45USB2.0
RJ-45	10M / 100M
	> 400/
I / O	4/ 4
	RSSI

材料	4-TNC
重量	0.000000
长度	0.15m
直径	0.07m
温度	
湿度	-20 + 70℃
压力	-40 + 85℃
风速	86kPa-108kPa
湿度	5-95%RH
防护等级	IP55

材料
重量
长度
直径
温度
湿度
压力
风速
湿度
防护等级



Banking management



Asset management



Retail management



Warehouse management



Vehicle management



Customs inspection