













C_____RFID__

| 000 | 0000000RFID000 |
|-----|---|
| | |
| | Dia55mm[Dia62mm[|
| 000 | LH / 125KHz; HF / 13.56MHz; UHF / 860MHz□ |
| | ISO 14443A / 1569; ISO 18000-6C□ |

| | 1 | | | | | | |
|--------|--|--|--|--|--|--|--|
| | If 125khz. | | | | | | |
| | GK4001\[\text{EM4200}\]\text{EM4100 / \\ \text{EM4102}\[\text{EM4550}\]\text{EM4069}\[\text{ATA5577}\]\text{ATA5567}\[\text{T5557}\]\text{Hitag 1}\[\text{Hitag 2}\]\text{Hitag \} | | | | | | |
| | S256 Hitag S2048 | | | | | | |
| | | | | | | | |
| | 1∏.Type1. | | | | | | |
| | Broadcom Topaz512[]454[][]; | | | | | | |
| | 2].Type 2 | | | | | | |
| | NXP NTAG213[]144[][] | | | | | | |
| | NXP NTAG215[[504][[]] | | | | | | |
| | NXP NTAG216□888□□□ MifareUltraLight®Ev1□48□□□ | | | | | | |
| | MifareUltraLight ® C 148 | | | | | | |
| | MIFARE OLI RALIGULIAL NXP B.VOODOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOOO | | | | | | |
| | 3[4] | | | | | | |
| | MÏFÄRE®DESFIRE®EV12K | | | | | | |
| | Mifare®Desfire®EV14K | | | | | | |
| | MIFARE®DESFIRE®EV18K | | | | | | |
| | MIFARE DESFIREDNXP B.V000000000000000000000000000000000000 | | | | | | |
| | 4 MIFARE® 1K | | | | | | |
| | Mifare[Mifare Classic[NXP B.V[]][] 5∏mifareplus®. | | | | | | |
| | MIFAREDMIFARE PLUSDNXP B.VDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDDD | | | | | | |
| | 6[]Fudan FM11RM08[]TI2048[]NXP icode SLI[]NXP ICODE SLIX[][] | | | | | | |
| | 7□SRT512 | | | | | | |
| | UHF 860-960MHz. | | | | | | |
| | ISO / IEC 18000-6C EPC Class1 Gen2[]ALI9662[]AD824[]AD803[]AD830[]U[[]G2XL[] | | | | | | |
| | UDDG2XMDUDGen2DMonza 3 ISO / IEC 18000-6BDUDDHSLDEM4324DD | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 00HF0UHF01M-10M03-10cm00000000 | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | 00000/00/00/000/000/000/000/000/000/ NFC /000000/0000 | | | | | | |
| | EXW[]FOB[]CIF[]CNF[] | | | | | | |
| 0000 | | | | | | | |
| | 7-12000005K00000 | | | | | | |
| 0000 | | | | | | | |
| 000000 | 100pcs / opp[]15 opp / ctn[] | | | | | | |
| | ISO9001-2008 SGS RoHS EN71 | | | | | | |
| 0000 | 6,000,000 pcs /□□ | | | | | | |
| MOQ□ | 500[PCS[]RFID[][] | | | | | | |
| | | | | | | | |

| | | | | | | | | | | | | r | Ħ | d | | | |
|--|--|--|--|--|--|--|--|--|--|--|--|---|---|---|--|--|--|
|--|--|--|--|--|--|--|--|--|--|--|--|---|---|---|--|--|--|

Packing



Package for Silicone Wristbands



Package for Soft PVC/ Paper Wristbands



Package for Woven Wristbands



Outside Carton Package

___rfid_____

Silicone RFID Wristband Production Process



Other Product You May Interest









NFC Tag









RFID Card







Company Introduction

Office

3,000 m² office, 250+ professional sales service you!















Shenzhen Great Creativity Smart Card Co.,Ltd.

Factory

12,000m2 clean work shop, more than 500 staffs, strict QC system, full set of advanced machines for all kinds of crafts production, ensuring each order will be taken cared fast and well.











