

CJ2505A UHF ISO18000-6C/6B
 920MHz 925MHz 840MHz 845MHz FCC 902MHz 928MHz ETSI 865MHz 868MHz JIP 916MHz
 920MHz 0dBm 30dBm
 Impinj R2000
 IP66
 ARM9 400MHz
 ISO18000-6B/6C
 Linux 2.6
 RJ-45/RS-232/RS-485/WIGAN

□□□□

□□	
□□□□	Linux 2.6
CPU	ARM9 400MHz
DDR	DDR 128M ROM 256M
□□□□	
□□	164□□×164□□×49.6□□
□□	1.0□□
□□	□PC
□□	□□24V/2.5A
UHF RFID	
□□	ISO18000-6B/6C
□□	FCC 902 928MHz 865 868MHz 920 925MHz 840MHz 845MHz
□□□□	0 30dBm(±1.5dBm)
□□□□	1dB □□
□□□□	□200kHz
□□□□□	≤±10ppm
□□□□	≤1.3:1
□□□□	RS-232 □RS-485 □□□□RJ45 □USB2.0
□□□□	□□□□□□□□
RJ-45 □□□□	10M/100M □□□
□□□□	>400 time/s
□□□□□□	1 □□□□□/2 □□□□□□
□□□□□	□□□□□□□□□□□□□□
□□	□□RSSI □□□□□□□□□□□□

RFID	RFID 6dBi
RFID	RFID 8m
RFID	RFID 4m
RFID	
RFID	-30~70°C
RFID	-45~85°C
RFID	86kPa~108kPa
RFID	5%~95%RH
RFID	IP54

UHF RFID



