



Spécifications du bracelet RFID en silicone à boucle fermée :

Nom du produit :	Bracelet en silicone RFID
Taille:	périmètre 157mm périmètre 184mm périmètre 195mm périmètre 228mm
Ébrécher:	LF 125 kHz, HF 13,56 MHz, UHF 860-960 MHz
Protocole:	ISO14443A, ISO15693, ISO7814, ISO7815, ISO18000-6C, etc.
Couleur du bracelet :	couleur personnalisée par PMS
Impression de logos :	sérigraphie, gravure laser, gaufrage, transfert thermique, etc.
Artisanat:	Impression de numéros (numéro de série et UID de puce, etc.), QR, code-barres, etc. Le programme de puce/encodage/verrouillage/cryptage sera également disponible (URL, TEXTE, Numéro et Vcard)
Caractéristiques:	Étanche, résistance à la chaleur -30--90 °C
Application:	Billetterie, soins de santé, voyages, contrôle d'accès et sécurité, pointage, stationnement et paiement, gestion des adhésions aux clubs/SPA, récompenses et promotions, etc.

Application de bracelet en boucle fermée RFID en silicone :



Options artisanales de bracelet en boucle fermée RFID en silicone :



1 C silk screen printing



3 C silk screen printing



laser engraved no color



laser engraved with color



embossed



heat transfer printing



divided color



mixed color



3D pattern



combination multi color



laser number no color



laser number with color



QR code



QR code



Bacode



laser LOGO on lock



glow in dark



Deboss With filling silver color



Deboss With filling gold color

