## Informations d'usine :

| | |
|---|---|
| Taille d'usine : | 3 000 à 5 000 mètres carrés |
| Pays/région de l'usine : | Étage 2-4, bâtiment E, zone industrielle de Yongda, route No.14 Rongfu, Guanlan, nouveau district de Longhua, Shenzhen, 518110 |
| Nombre de lignes de production : | 6 |
| Fabrication sous contrat: | Service OEM offert, service de conception offert, étiquette d'acheteur offerte |
| Valeur de production annuelle : | 50 millions de dollars américains - 100 millions de dollars américains |

# Certificates & Rewards

## Description du support de bague NFC :

| | |
|---|---|
| Nom du produit : | Support d'anneau de téléphone NFC pour partage de médias sociaux |
| Les fonctions: | * Visitez l'URL d'un site Web<br>* Partager un fichier texte<br>* Associer avec un appareil Bluetooth<br>* Lancer une application spécifique<br>* Connectez-vous à un réseau wifi avec des informations d'identification<br>* Déclenchez une domotique intelligente<br>* Activer/Désactiver les paramètres du téléphone (alarme, sonnerie, etc.)<br>* Envoyer un message SMS |
| Taille: | Dia25mm/30mm ou personnalisé. |
| Impression: | Impression personnalisée du LOGO 4C ou numéro de série, code QR |
| Anti-métal : | Peut être anti-métal ou normal |
| Contrôle CQ : | Inspecter à 100 % avant l'emballage, inspecter sur place avant l'expédition |

| Chip type | Protocal | Capacity | Anti collision | Function |
|---|---|---|---|---|
| NTAG® 213 | ISO14443A | 180 Byte | NO | Read/write |
| NTAG® 215 | | 540 Byte | NO | |
| NTAG® 216 | | 924 Byte | NO | |
| NTAG® are registered trademarks of NXP B.V. and are used under license. | | | | |
| | | | | |
| MIFARE Classic® 1K | ISO14443A | 1KB | NO | Read/write |
| MIFARE Classic® 4K | | 4KB | NO | |
| MIFARE Ultralight® EV1 | | 640 Bit | NO | |
| MIFARE Ultralight® C | | 1184 Bit | NO | |
| MIFARE and MIFARE Classic® are registered trademarks of NXP B.V. and are used under license. | | | | |
| MIFARE and MIFARE Ultralight® are registered trademarks of NXP B.V. and are used under license. | | | | |
| | | | | |
| MIFARE Plus® 1K | ISO14443A | 1KB | NO | Read/write |
| MIFARE Plus® 2K | | 2KB | NO | |
| MIFARE Plus® 4K | | 4KB | NO | |
| MIFARE and MIFARE Plus® are registered trademarks of NXP B.V. and are used under license. | | | | |
| | | | | |
| MIFARE® DESfire® EV1 2K | ISO14443A | 2KB | NO | Read/write |
| MIFARE® DESfire® EV1 4K | | 4KB | NO | |
| MIFARE® DESfire® EV1 8K | | 8KB | NO | |
| MIFARE® DESFire® are registered trademarks of NXP B.V. and are used under license. | | | | |
| | | | | |
| ICODE® SLIX | ISO15693 | 1KB | Yes | Read/write |
| ICODE® SLIX-S | | 2KB | Yes | |
| ICODE® SLIX-L | | 512 Bits | Yes | |
| ICODE® SLIX-M | | 1KB | Yes | |
| ICODE® are registered trademarks of NXP B.V. and are used under license. | | | | |

# Product Display

## Epoxy

## Regular