

RDM530 RFID reader supports ISO14443A/B, ISO15693, ISO18092 standard cards. It connects with the PC machine and device through RS232, USB, TCP/IP or wireless WIFI interface. Free Software Development Kit will be provided for second integration. RDM530 series of reader is a necessary front-end processing device for developing contactless card related application products and system integration. It is widely used in the smart card management systems fields.

Product Specifications:

Product Type	HF 13.56Mhz RFID Reader
Material	ABS
Size	100mm*100mm*27mm
Frequency	13.56Mhz
Protocol	ISO/IEC14443A, ISO/IEC14443B, ISO/IEC15693
Support Card	Mifare S50/S70/Ultralight, Mifare desfire, I-code 2, TI RFID Tag-it HF-I, etc
Reading Range	>5CM□Depends on the label size□
Communication Interface	RS232, USB-UART/USB-HID
Power Consumption	DC 5V(±5%)
Accessories	USB (RS232) Cable, disk(SDK, Demo, User's manual)
Applications	E-government, Bank and payment, Electronic medical, Cyber security, Access control, Wallet and bonus points, Public transit, etc
Packaging Details	Reader is protected by plastic bag into carton box, 1piece per box, box size: 17*12*6cm
Lead Time	Shipped in 5 days after payment

Product Image:



Small size,
Easy to operate

Protected by plastic bag
into carton box

