



Specifiche del braccialetto a circuito chiuso in silicone RFID:

Nome del prodotto:	Bracciale in silicone RFID
Misurare:	perimetro 157mm perimetro 184mm perimetro 195mm perimetro 228mm
Patata fritta:	LF 125 kHz, HF 13,56 MHz, UHF 860-960 MHz
Protocollo:	ISO14443A, ISO15693, ISO7814, ISO7815, ISO18000-6C ecc
Colore del cinturino:	colore personalizzato per PMS
Stampa del logo:	serigrafia, incisione laser, rilievo, trasferimento di calore ecc.
Mestiere:	Stampa di numeri (numero di serie e UID chip ecc.), QR, codici a barre ecc. Saranno disponibili anche programmi/codifica/blocco/crittografia con chip (URL, TESTO, numero e Vcard)
Caratteristiche:	Impermeabile, resistenza al calore -30--90 °C
Applicazione:	Biglietteria, assistenza sanitaria, viaggi, controllo accessi e sicurezza, rilevazione presenze, parcheggio e pagamento, gestione iscrizioni a club/SPA, premi e promozioni, ecc.

Applicazione del braccialetto a circuito chiuso in silicone RFID:



Opzioni artigianali per braccialetti ad anello chiuso in silicene RFID:



1 C silk screen printing



3 C silk screen printing



laser engraved no color



laser engraved with color



embossed



heat transfer printing



divided color



mixed color



3D pattern



combination multi color



laser number no color



laser number with color



QR code



QR code



Bacode



laser LOGO on lock



glow in dark



Deboss With filling silver color



Deboss With filling gold color

