

CJ2504B 4UHF RFIDUHF RFIDISO18000-6C / 6B2
 920MHz925MHz /
 840MHz845MHzFCC902MHz928MHzETSI865MHz868MHzJP916MHz920MHz
 0dBm33dBm

Impinj R2000
 ARM9400MHz
 ISO18000-6B / 6C
 Linux 2.6
 RJ-45 / RS-232 / RS-485 / USB2.0 / Wiegand
 RSSI
 BluetoothWIFI

Table

OS	Linux 2.6
CPU	ARM9,400MHz
Memory	DDR SDRAM128MROM256M
Dimensions	255mm×145mm×35mm
Weight	1.4g
Power	DC 24V / 2.5A
UHF RFID	
Protocol	ISO18000-6B / 6C
Frequency	FCC902928MHz; ETSI865868MHz GB920925MHz840845MHz
Power	033dBm±1.5dBm
Antenna	1dB
Bandwidth	<200kHz
Accuracy	±10ppm
Interface	RS-232RS-485wiegandRJ45USB2.0
IO	
RJ-45	10M / 100M
Temperature	> 400
I / O	4 / 4
Support	support
RSSI	

□□□□□□□□□□	4□TNC□□□□□□□□□□
□□□□	□□□□□□□□
□□□□	0□15m□□□□□□□□□□□□□□□□
□□□□□□	0□7m□□□□□□□□□□□□□□□□
□□□□	
□□□□	-20□+ 70°C
□□□□	-40□+ 85°C
□□□	86kPa□108kPa
□□	5□95□RH□□□□□□
□□□□□	IP55

□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□
□□□□□□
□□□□□□□□□□□□□□□□



Banking management



Asset management



Retail management



Warehouse management



Vehicle management



Customs inspection