

**RFID**

1. Specification

NXP Ntag213 Mifare S50 NXP NXP C 512  
ISO 14443A  
13.56MHz / HF  
R / W 100000  
106  
3 10

2. Profile

PVC / PET  
85.5 \* 54 \* 0.84

3. Working

5 10  
-25°C 50°C  
20 90 RH  
-40°C 65°C

4. Craft

- preprinting CMYK &
- signature
- magnetic 3000OE 2750OE 4000OE
- barcode Code39 Code128 EAN8 EAN13
- numbering
- encoding

5. Application

6. Informaton

10boxes / 14 / 200 / 22.5 \* 9.3 \* 6  
Delevery 10K 5-7  
DHL  
EXW FOB CIF CNF  
TT  
6,000,000pcs /  
ISO9001-2008 SGS ROHS EN71

**RFID**



□□□□□□□□

## Related Products



			
1.NFC Stickers	2.NFC Epoxy Tags	3.Silicone Wristbands (Adjustable Type )	4.Silicone Wristbands (Full Sealed Type)
			
5.Woven NFC Wristbands	6.NFC Keyfobs	7. NFC PVC Tags	8. Anti-metal Stickers

□□□□□□□□



SGS Test Report



ISO9001 - 2008 Certificate

SGS ISO9001 2000 15 RFID RFID NFC  
OPPO NXP

**RFID FAQ**

- Q1
  - A1 Chuangxinjia 15 NFC Telecoming
  - Q2
  - A2 UPS TNT DHL EMS
  - Q3
  - A3 L / C T
  - Q4
  - A4 8 2-5days
  - Q5 / / QR
  - A5
  - Q6
  - A6 1 3
  - Q7 RFID MOQ
  - A7 MOQ 500
  - Q8 RFID
  - A8 OEM ODM RFID MOQ
  - Q9
  - A9
  - Q10 RFID
  - A10 QC RFID
- ISO9001-2008 SGS ROHS EN71

**RFID NFC**

- \* RFID NFC
- \* 10 2012 Entrepreneurs
- \* ISO9001-2008 ROHS SGS EN71

\*XXXXXXXXXXNXPXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XX  
XXXXsharon@cxjrfid.com / sharon@nfctagfactory.com