

RFID Tag Specifications

Quantity	1 RFID Tag
Material	PVC / PET
Dimensions	250 * 30 * 14 mm
Frequencies	LH/125 KHz, HF/13.56 MHz, UHF/860 MHz
Standards	ISO 14443A, ISO 1569, ISO 18000-6 C
Chip Options	-LF(125KHz): TK4100, EM4200, ATA5577 -HF(13.56MHz): NXP Ntag213, Mifare S50, NXP Ultralight, NXP C, Broadcom 512 -UHF(860-960MHz): Ucode, G2XM, G2XL, H3
Read Range	3-10 cm (HF), up to 100m (UHF)
Temperature	PVC: -30 ° C ~ 75 ° C PET: -30 ° C ~ 220 ° C
Customization	Logo, Text, Barcodes, etc.
Incoterms	EXW, FOB, CIF, CNF, TT, L/C
Quantity	5 k 7-12 tags
Shipping	Express (DHL, FEDEX)
Packing	100 tags/OPP, 30 OPP/CTN
Certifications	ISO9001, SGS, ROHS, EN71.

RFID Tag Specifications



□□□□□□

Related Products



			
1.NFC Stickers	2.NFC Epoxy Tags	3.Silicone Wristbands (Adjustable Type)	4.Silicone Wristbands (Full Sealed Type)
			
5.Woven NFC Wristbands	6.NFC Keyfobs	7. NFC PVC Tags	8. Anti-metal Stickers

□□□□

