□□□□□□: NXP Ntag213 Mifare S50 NXP Ultralight NXP □□□ C Broadcom □□□□ 512 □□□ □□: NFC □□□ 2 □ ISO 14443a □□□□□□□□ □□□/□□□□: 13.56 mhz/HF□ R/w: || || || 100000 || | EPPROM: 64 0000192 0000144 0000512 00001 k 00000000 EPPROM 0000000 0000: 3-10 cm 2. 3. □□□□:-25 ° 50 °C □□: 20 ~ 90% RH □□□□:-40 ° 65 °C 4. 00000 500000 חחחח: חחחחח express(DHL,FEDEX) חחחחח OCCUPIED CONFINE CONFI □□□□: 6,000□000pcs/□□ | iso 9001-2008 | SGS|| ROHS|| EN71||


00000 0000000 **NFC** 00 00000000




Extensive Experience with NFC











	NXP Mifare Ultralight	NXP Mifare Ultralight C	NTAG213	Topaz512	Mifare 1k
NFC Type	Type 2	Type 2	Type 2	Type 2	Type 2
User memory	64 byte	192 byte	144 byte	512 byte	1k byte
URL Length	41 Characters	132 Characters	132 Characters	132 Characters	256 Characters
Text Length	39 Characters	130 Characters	130 Characters	130 Characters	709 Characters
Data Example	Short URL Phone Number Short email address Short Text	Short URL Phone Number Short email address Short Text	Long URL Phone Number Email address Text Small Vcard	Long URL Phone Number Email address Text Small Vcard	Full Voard
Lockable	Yes	Yes	Yes	Yes	Technically No
Formatting	Blank or NDEF formatted	Blank or NDEF formatted	NDEF Formatted	Blank or NDEF formatted	Blank or NDEF formatted