□□□□:

□□□□□□□□□□:	3,000□5,000□□□□□□□
□□□□/□□:	2-4□□E□□□□□□□□□No.14 Rongfu Road□Guanlan□Longhua New District□Shenzhen□518110
□□□□□□:	6
□□□□:	OEM □□□□□□□□□□□□□ □□□□□□□□□□□□□ □□□□□□□
□□□□□:	5,000□□□□1□□□

Certificates & Rewards

NFC □□□□□□□□□□:

□□□□	□□□□□ □□□□ □□□ NFC □□□□□ □□□□
□□□	* □□□□□□□ URL □□□□□□□□ * □□□□□□□□□□□□□ * Bluetooth □□□□□□□□□□□□ * □□□□□□□□□□□ * □□□□□□□□□ Wi-Fi □□□□□□□□□□□□ * □□□□□□□□□□□□□□□□□□□□□□□□ * □□□□ (□□□□□□□□□□□) □□□/□□□□□□□□□□ * SMS□□□□□□□□□
□□□□	Dia25mm/30mm □□□□□□□□□□
□□□	□□□□4C□□□□□□□□□□□□□□□□QR□□□
□□□□□□:	□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□:	□□□□□□□□□□□□□□□□□□□□□□

Chip type	Protocal	Capacity	Anti collision	Function
NTAG® 213	ISO14443A	180 Byte	NO	Read/write
NTAG® 215		540 Byte	NO	
NTAG® 216		924 Byte	NO	
NTAG® are registered trademarks of NXP B.V. and are used under license.				
MIFARE Classic® 1K	ISO14443A	1KB	NO	Read/write
MIFARE Classic® 4K		4KB	NO	
MIFARE Ultralight® EV1		640 Bit	NO	
MIFARE Ultralight® C		1184 Bit	NO	
MIFARE and MIFARE Classic® are registered trademarks of NXP B.V. and are used under license.				
MIFARE and MIFARE Ultralight® are registered trademarks of NXP B.V. and are used under license.				
MIFARE Plus® 1K	ISO14443A	1KB	NO	Read/write
MIFARE Plus® 2K		2KB	NO	
MIFARE Plus® 4K		4KB	NO	
MIFARE and MIFARE Plus® are registered trademarks of NXP B.V. and are used under license.				
MIFARE® DESfire® EV1 2K	ISO14443A	2KB	NO	Read/write
MIFARE® DESfire® EV1 4K		4KB	NO	
MIFARE® DESfire® EV1 8K		8KB	NO	
MIFARE® DESFire® are registered trademarks of NXP B.V. and are used under license.				
ICODE® SLIX	ISO15693	1KB	Yes	Read/write
ICODE® SLIX-S		2KB	Yes	
ICODE® SLIX-L		512 Bits	Yes	
ICODE® SLIX-M		1KB	Yes	
ICODE® are registered trademarks of NXP B.V. and are used under license.				

Product Display

Epoxy

Regular