

□□□□□

□□□□□□ □□:	3,000□5,000□□□□□□
□□□□/□□:	2-4□□E□□□□□□□□□□No.14 Rongfu Road□Guanlan□Longhua New District□Shenzhen□518110
□□□□□□:	6
□□□□:	OEM □□□□□□□□□□ □□□□□□□□□□ □□□□□□
□□□□□:	5,000□□□□1□□□



UHF RFID □□□□□□□□□□:

□□□□□	UHF ABS □□□□□□□□
□□□	ABS
□□□□	□□□□□ H3□M4E□M4D□M4QT□MR6
□□□	860□960MHz
□□:	5□12mm
□□□□	40mm*40mm □□□□□□□□□□
□□□□□□:	0.5-10 m (□□□□□□□□□□□□□□□□)
□□□□□□□:	100000□
□□□□□□	-25°C□65°C
□□□□□□□:	10□
□□□□□□□:	□□□□□□□ □□□□□□□□□□ □□□□□□□□□□
□□□	□□□□□□□ □□□□□□□□□□ □□□□□□□□□□
□□□□:	□□□□□□□□□□□□□□□□□□□□

PPS Material

Storage Temperature: -40°C to +85°C

Operation Temperature: -40°C to +85°C



ISO18000-6C Classic 1 Gen 2





