CJ2503A UHF RFID 000000000000000000000000000000000000
$920 MHz - 925 MHz _ 840 MHz - 845 MHz _ FCC: 902 MHz - 928 MHz _ ETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz _ SETSI: 865 MHz - 868 MHz _ JP: 916 MHz - 928 MHz - 92$
920MHz
Impinj R2000 RF [][][][][][][]
IP6600000000000000000000000000000000000
CPU: ARM9 [][][][][][][] 400MHz
ISO18000-6B/6C
0000 Linux 2.6 0000000 000000000000000000000000000
RJ-45/RS-232/RS-485/Wiegand [][][][][][][][][][][][][][][][][][][]
9dBi

	290mm×290mm×115mm
	□2.5kg(□□□□□)
	□□PC
	DC24V/2.5A
0000000	20W(□□30dBm)
UHF RFID	
	ISO18000-6B/6C
	GB:920[]925MHz[]840MHz[]845MHz FCC[]902[]928MHz ETSI[]865[]868MHz JP: 916[]920MHz[]]]]]]]]
	0_33dBm()
	1dB
	□200kHz
	≤±10ppm
	RJ-45_RS232_RS485
RJ-45	10M/100M
RS-232000000	
1/0 0000000	
	>400 time/s
0000	9dBi 000000000000000000000000000000000000
	0010m000000000000000000000000000000000

0000	0_5m
	-30∏70°C
	-40∏85°C
	10%[]95%RH [][][][]



UHF RFID





