

RFID

1.Specification

RFID : NXP Ntag213, MIFARE S50, NXP , NXP C, 512
: ISO 14443A
/ : 13.56 / HF.
R / W : 100000
: 106 kbit / s.
: 3~10cm

2.Profile

: PVC / PET /
: , ,
: 85.5 * 54 * 0.84mm

3.Working

: 5 ~ 10
: -25 °C ~ 50 °C
: 20 % ~ 90 % RH
: -40 °C ~ 65 °C

4.Craft

-preprinting : CMYK & ;
-signature
-magnetic : 3000OE, 27500OE, 40000OE
-barcode : CODE39, Code128, EAN8, EAN13,
-numbering : , ,
-encoding

5.

, , , ,

6. Informaton

: 10boxes / , 14kg / (, 200PCS / 22.5 * 9.3 * 6cm)
Delevery : 10K 5-7
: (DHL,), ,
: EXW, FOB, CIF, CNF
: TT, ,
: 6,000,000pcs /
: ISO9001-2008, SGS, ROHS, EN71.

RFID



☐☐ ☐☐☐ ☐☐☐☐

Related Products



			
1.NFC Stickers	2.NFC Epoxy Tags	3.Silicone Wristbands (Adjustable Type)	4.Silicone Wristbands (Full Sealed Type)
			
5.Woven NFC Wristbands	6.NFC Keyfobs	7. NFC PVC Tags	8. Anti-metal Stickers

☐☐☐ ☐☐☐☐ ☐☐

☐☐☐ ☐☐☐☐☐ ☐☐, ☐☐☐ ☐☐ ☐☐☐☐☐. ☐☐ ☐☐☐☐☐☐☐☐☐☐☐☐☐!
☐☐☐ : sharon@cxjrfid.com / sharon@nfctagfactory.com