

RFID VIP

1.Specification.

IC : NXP Ntag213, MIFARE S50, NXP C, 512
ISO 14443A
/ : 13.56 / HF.
 : 3~10cm

2.Profile

: PVC / PET /
 : , ,
 : 85.5 * 54 * 0.84mm

3.Working

5~10
 : -25 °C -50 °C
 : 20 % -90 % RH
 : -40 °C -65 °C

4.Craft

-preprinting : CMYK & ;
-signature
-magnetic : 300OE, 2750OE, 4000OE
-barcode : CODE39, Code128, EAN8, EAN13,.
-numbering : , ,
-encoding

RFID 5. .

IC , , , , ,

6.Package

RFID , 10 / , 14kg / (, 200 / 22.5 * 9.3 * 6cm).
 : 10K 5-7 .
 : (DHL,), , .
 : EXW, FOB, CIF, CNF
 : TT, , .
 : 6,000,000 /
 : ISO9001-2008, SGS, ROHS, EN71.

RFID VIP



RFID VIP

RFID, 10 / , 14kg / (, 200 / 22.5 * 9.3 * 6cm) .

Packing



OPP Bag for Individual Card



250/200 pcs Cards with Clear Paper



Inner Box Package



Outside Carton Package

RFID

(RFID) 00 0000 0000 00 0 0000.

RFID 0000 000000, 00 0000 00 000000 00 0 0000. 00 0000 00 0000 0000 RFID 0000 00 0000 0000 0000 0000 0000 0000 0000 0000 0000 0000.

00 00

00 00 00 00 0000 00 (0), (0) 15 0 0000 000000 00 00 RFID 00 / NFC 00 00 000000. 0000 00 0000 RFID 00 / NFC 00 00, 0000 0 0000 00, 00, OPPO, 000000 0000 0 0 RFID / NFC 00, RFID ID 00, RFID 00, NFC 0000, NFC 00,.

RFID 0000 00 0000 0000 000000 0000 0 000000 000000 000000 <http://www.nfctagfactory.com/> 00 0000 0000 00 0 0000 00.