## **NFC** | | | | | | :



#### 

#### 

#### 

#### 

### **NFC** [[[[]] [[]] :

:	
<u> </u>	□□□ □□, PVC
<u> </u>	25mm □ , 35 * 35mm, 50 * 50mm, 27 * 42mm, 85 *
	54mm

	LF 125KHz
	GK4001, EM4200, EM4100 / EM4102, EM4550, EM4069,
	ATA5577, ATA5567, T5557, HITAG 1, HITAG 2,
	HITAG S256, HITAG S2048 □
	HF 13.56MHz
	1). □□ 1
	, 55
	Broadcom Topaz512 (454 □□□);
	2). 🔲 2
	NXP Ntag213 (144 □□□)
	NXP Ntag215 (504 □□□)
	NXP Ntag216 (888 □□□)
	MIFARE Ultralight®EV1 (48 □□□)
	MIFARE Ultralight®C (148 ППП)
	MIFARE [] MIFARE Ultralight[] NXP B.V.[] [] [] [] [] []
	3)
	MIFARE® DESFire® EV1 2K
	MIFARE® DESFire® EV1 4K
	MIFARE® DESFire® EV1 8K
	MIFARE DESFire NXP B.V. 00 0000 00000 00000.
	4) MIFARE® (1K □□□)
	MIFARE [] MIFARE Classic[] NXP B.V.[] [][][][].
	5) MIFAREPlus®
	MIFARE [] MIFARE Plus[] NXP B.V.[] [] [] [] [] [] [] [] [] [] [] [] [] [
	6) FUDAN FM11RM08, TI2048, NXP ICODE SLI, NXP
	ICODE Slix [] []
	7) SRT512
	UHF 860-960MHz
	ISO / IEC 18000-6C EPC Class1 Gen2 : ALI9662, AD824,
	AD803, AD830, U ∏∏ G2XL,
	U □□ G2XM, U □□ GEN2, Monza 3
	ISO / IEC 18000-6B : U □□ HSL, EM4324 □
	100 PC / 00, 10 00 / 00, 20 00 00 / 00
	5-7 🛮 🖂 🖂
00 00 :	□□ (DHL, FEDEX), □□□□, □□□

	EXW (DD), FOB (DD), CIF, CNF
00 00 :	TT, L / C, 000 000, 00 00 0
MOQ:	500 □
00 0 00 :	

# 00 000:







