00 00 00 000 **NFC** 00 00000 000 0 0 □ □□: NXP Ntag213, Mifare S50, NXP □□□, NXP □□□ C, □□□ □ □ 512 □. □□: NFC 2 □□□ ISO 14443A □□□□. $\square\square\square/\square\square\square$: 13.56 m h z/HF. R/w: | | | | | | 100000 | | | | | | | | | | EPPROM: 64 nnn, 192 nnn, 144 nnn, 512 nnn, 1 k nnn n. nn EPPROM nn nnnn. 00 00: 3-10 cm 00 00 0 000 00 00 000. 2. □: 25 mm □, 35 * 35 m m, 43 * 26 mm, 50 * 50 m m, 86 * 54mm, □ □. □□: 0.2-0.5 m m □□ 0.8-1 m m, □□ □□□ □□. 3. 00 00: 5 ~ 10 0 00 000 00 00 000. □□ □□:-25 °C-50 °C □□: 20%-90% RH ПП ПП:-40 °C ~ 65 °C 4. 🔲 5000.00 0 00 00 Delevery [] : [] [] [] 10 k 5-7 [] []. $\square \square \square \square : express(DHL,FEDEX), \square \square$ □□ □□: FOB, CIF, CNF, EXW □□ □□: 6, 000, 000pcs/□. □□□: ISO9001-2008 □, SGS, ROHS, EN71.

00 00 00 000 **NFC** 00 00000 000 0 0




6. NFC 00/NFC 000/NFC 000 00 0000


Extensive Experience with NFC











NFC | | | | | | | | | | | | |

NFC 000 000 000 0 0000.?

| | NXP Mifare Ultralight | NXP Mifare Ultralight C | NTAG213 | Topaz512 | Mifare 1k |
|--------------|---|---|--|--|----------------|
| NFC Type | Type 2 | Type 2 | Type 2 | Type 2 | Type 2 |
| User memory | 64 byte | 192 byte | 144 byte | 512 byte | 1k byte |
| URL Length | 41 Characters | 132 Characters | 132 Characters | 132 Characters | 256 Characters |
| Text Length | 39 Characters | 130 Characters | 130 Characters | 130 Characters | 709 Characters |
| Data Example | Short URL Phone Number Short email address Short Text | Short URL Phone Number Short email address Short Text | Long URL Phone Number Email address Text Small Vcard | Long URL Phone Number Email address Text Small Vcard | Full Vcard |
| Lockable | Yes | Yes | Yes | Yes | Technically No |
| Formatting | Blank or NDEF formatted | Blank or NDEF formatted | NDEF Formatted | Blank or NDEF formatted | Blank or NDEF |