

□□□ □ :	<p>LF 125KHz□ GK4001, EM4200, EM4100 / EM4102, EM4550, EM4069, ATA5577, ATA5567, T5557, HITAG 1, HITAG 2, HITAG S256, HITAG S2048 □</p> <p>□□□ 13.56MHz□ 1) .Type1 □□□ Topaz512 (454 □□□); 2) .Type 2 NXP Ntag213 (144 □□□) NXP Ntag215 (504 □□□) NXP Ntag216 (888 □□□) MIFARE Ultralight®EV1 (48 □□□) MIFARE Ultralight®C (148 □□□) MIFARE □ MIFARE □□□□ NXP BV□ □□ □□□□ □□□□ □□ □□ □□□□□.</p> <p>3) 4□ □□ MIFARE® DESFire® EV1 2K MIFARE® DESFire® EV1 4K MIFARE® DESFire® EV1 8K MIFARE DESFire□ NXP BV□ □□ □□□□ □□□□ □□ □□ □□□□□.</p> <p>4) MIFARE®□ (1K)□ □□□ MIFARE □ MIFARE □□□□ NXP BV□ □□ □□□□□□</p> <p>5) MIFAREPlus® MIFARE □ MIFARE Plus□ NXP BV□ □□ □□□□ □□□□ □□ □□ □□□□ □.</p> <p>6) □□ FM11RM08, TI2048, NXP ICODE SLI, NXP ICODE Slix □ □</p> <p>7) SRT512</p> <p>UHF 860-960MHz ISO / IEC 18000-6C EPC □□□ 1 □□ : ALI9662, AD824, AD803, AD830, U □□ G2XL, U □□ G2XM, U □□ GEN2, □□ 3 ISO / IEC 18000-6B : U □□ HSL, EM4324 □</p>
□□ :	□□ □□ □□, □□□□ □□□□, □□ □□, □□□□ □□ □□, □□□□ □□□□
□□□ :	100 □ / □□, 10 □□ / □□, 20 □□ / □□
□□ □□ :	□□ 5-7 □□□□
□□ □□ :	□□□□□ (DHL, □□□□)□, □□□□□, □□□□
□□ □□ :	□ EXW (□□), FOB (□□), CIF, CNF□
□□□□ □□ :	TT□ □□□, L / C, □□□□ □□□□, □□ □□ □
MOQ :	500 □
□□ □□ :	□□□□ □□□□ □ □□ □□ □□□□□ □□ □□





□ □□□ □□ □□, □□ □ □□□□□.