

□□ □□:

□□ □□:	3,000-5,000 □□ □□
□□ □□/□□:	518110 □□ Longhua New District Guanlan, No.14 Rongfu Road, Yongda Industrial Zone, E Building 2-4□
□□ □□ □:	6
□□□□ □□:	OEM □□□□ □□, □□□□ □□□□ □□, □□□□ □□ □□
□□ □□ □□:	5□□ □□ - 1□ □□



UHF RFID □□□□ □□ □□:

□□:	UHF ABS □□ □□ □□
□□:	ABS
□□:	□□□□ H3, M4E, M4D, M4QT, MR6
□□:	860~960MHz
□□:	5-12mm
□□:	40mm*40mm □□ □□□□ □□□□
□□ □□:	0.5-10m(□□ □ □□□ □□ □□)
□□ □□□:	100000□
□□ □□:	-25°C ~ 65°C
□□□□ □□ □□:	10 □
□□:	□□ □□ □□ □□□□ □□ □□ □□ □□ □□ □□□□□□
□□:	□□ □□ □□, □□ □ □□□□□ □□ □□□□ □ □□
□□:	□□ □ □□ □□□ □□□ □ □□□□.

PPS Material

Storage Temperature: -40°C to +85°C

Operation Temperature: -40°C to +85°C



ISO18000-6C Classic 1 Gen 2





