

RDM530 RFID reader supports ISO14443A/B, ISO15693, ISO18092 standard cards. It connects with the PC machine and device through RS232, USB, TCP/IP or wireless WIFI interface. Free Software Development Kit will be provided for second integration. RDM530 series of reader is a necessary front-end processing device for developing contactless card related application products and system integration. It is widely used in the smart card management systems fields.

Product Specifications:

| | |
|-------------------------|--|
| Product Type | HF 13.56Mhz RFID Reader |
| Material | ABS |
| Size | 100mm*100mm*27mm |
| Frequency | 13.56Mhz |
| Protocol | ISO/IEC14443A, ISO/IEC14443B, ISO/IEC15693 |
| Support Card | Mifare S50/S70/Ultralight, Mifare desfire, I-code 2, TI RFID Tag-it HF-I, etc |
| Reading Range | >5CM□Depends on the label size□ |
| Communication Interface | RS232, USB-UART/USB-HID |
| Power Consumption | DC 5V(±5%) |
| Accessories | USB (RS232) Cable, disk(SDK, Demo, User's manual) |
| Applications | E-government, Bank and payment, Electronic medical, Cyber security, Access control, Wallet and bonus points, Public transit, etc |
| Packaging Details | Reader is protected by plastic bag into carton box, 1piece per box, box size: 17*12*6cm |
| Lead Time | Shipped in 5 days after payment |

Product Image:



Small size,
Easy to operate

Protected by plastic bag
into carton box

